## (19) World Intellectual Property Organization International Bureau





#### (43) International Publication Date 29 March 2001 (29.03.2001)

PCT

# (10) International Publication Number WO 01/22177 A1

- (51) International Patent Classification<sup>7</sup>: G05B 15/00, 19/414, G06F 15/16, 17/60, 19/00, A01G 25/16
- (21) International Application Number: PCT/AU00/01158
- (22) International Filing Date:

22 September 2000 (22.09.2000)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

- PQ 2993 22 September 1999 (22.09.1999) AU
- (71) Applicant (for all designated States except US): IRRIGATION CONTROL NETWORKS PTY LTD [AU/AU]; C/- Hood Sweeney Pty, 110 Hutt Street, Adelaide, S.A. 5245 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): TOWNSEND, James, Dunstone [AU/AU]; 104 Main Road, Hahndorf, S.A. 5425 (AU).


- (74) Agent: MCMASTER OBERIN ARTHUR ROBINSON & HEDDERWICKS; Stock Exchange Centre, 530 Collins Street, Melbourne, VIC 3000 (AU).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published:

With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IRRIGATION CONTROL SYSTEM



(57) Abstract: A method for remote management of a plurality of irrigation sites (90, 90) associated with clients who are responsible for the management of the sites (90, 90), each site (90) having one or more controllers (40, 40) adapted to turn on/off switching devices for irrigation equipment within the site (90), each controller (40) being adapted to execute a controller program and having controller memory for storing the controller program, the method comprising: (a) receiving from one of the clients, and storing in a host computer system (10), parameters for a site management program for one of the sites (90, 90) with which the client is associated, the preferred method of communication being the internet (100); (b) generating a controller program for each controller (40) of the site (90), the controller program being adapted to implement the controller's (40) role in the site management program for the site (90); (c) transmitting the controller programs to the respective controller memories of the controllers (40, 40); and (d) communicating with the controllers (40, 40) to initiate execution of the controller programs in accordance with the site management programs.

a y w w w

WO 01/22177 PCT/AU00/01158

#### Irrigation control system

#### Field of the invention

5

10

The invention relates to an irrigation control system for remote management (including programming and/or control) of irrigation sites. More particularly the invention relates to a control system for remote management of switching devices for irrigation equipment.

#### Background of the invention

It is known to provide remote control of site-installed irrigation equipment. However, the known methods generally require the person responsible for the management of the irrigation site to operate and maintain suitable hardware and/or software to effect the remote control. With the increasing complexity of computer systems there is a need to provide a more efficient system of remote control whereby the person responsible for the management of the irrigation site is not required to operate and maintain, or to operate and maintain as much, hardware and/or software to effect the remote control.

#### Summary of the invention

- 15 According to an aspect of the present invention, there is provided a method for remote management of a plurality of irrigation sites associated with clients who are responsible for the management of the sites, each site having one or more controllers adapted to switch switching devices for irrigation equipment within the site, each controller being adapted to execute a controller program and having controller memory for storing the controller program, the method comprising:
  - receiving from at least one of the clients, and storing in a host computer system,
    parameters for a site management program for one of the sites with which the client
    is associated;
- (b) generating a controller program for each controller of the site, the controller

  program being adapted to implement the controller's role in the site management program for the site;
  - (c) transmitting the controller programs to the respective controller memories of the controllers; and
- (d) communicating with the controllers to initiate execution of the controller programs
   30 in accordance with the site management programs.

10

15

20

25

30

The method enables clients responsible for one or more irrigation sites to outsource the responsibility for all or part of the hardware and/or software operation and maintenance that is necessary to effect remote control of switching devices for irrigation equipment within the client's site. In particular, the method may be operated as a service to clients responsible for one or more sites.

In a preferred form of the present invention, the client may enter a website operated by the operator of the method to program, and/or reprogram, the site management program for the client's site or sites.

Any suitable form of switching device for irrigation equipment may be used. Typically, the switching devices will include relays and/or triacs.

To enable a site management program to be manually overridden, the method may further comprise the step of communicating with a controller to halt execution of the controller's controller program following receipt of a stop command from a client responsible for the management of the site containing the controller, or from a or a person having the client's authority to issue the stop command.

To enable a site management program to have additional functionality to the programs in the controllers, the method may further comprise the step of communicating with a controller to halt execution of the controller's controller program following the generation of a stop command by a computer system implementing a site management program for the site containing the controller. Typically, the site management program may cause a stop command to be issued if rain is detected in the site.

It is desirable to enable the site management program to be readily amended. Accordingly, the method preferably further comprising the steps of receiving parameters in respect of amendments to a site management program for a site from the client responsible for the management of the site or from a person having the client's authority to communicate the parameters, generating a new controller program for each controller of the site that is affected by the amendments, and transmitting the new controller programs to the respective controller memories.

In order to make the system secure, the method may further comprise the steps of providing each client with a unique identifier, and receiving an identifier from a person

30

prior to implementing parameters received from the person to verify that the person is the client or has the authority of the client to communicate the parameters.

To readily enable clients to program the site management program, or to amend it, the method may further comprise the step of supplying the clients with software enabling the clients to effect the communication of the parameters. This may be effected by enabling the client to download the software from a website operated by the operator of the method.

The site management program of the method may include variable control logic that is in dependence on external data. The external data may be, or include, meteorological data. It may be, or include, Doppler radar data.

According to another aspect of the present invention, there is provided a host computer 10 system for remote management of a plurality of irrigation sites associated with clients who are responsible for the management of the sites, each site having one or more controllers adapted to switch switching devices for irrigation equipment within the site, each controller being adapted to execute a controller program and having controller memory for storing the controller program, the host computer system servicing a plurality of clients and 15 being adapted to communicate with the controllers and with client devices whereby to enable a client, or a person having the client's authority, to communicate parameters for a site management program to the host computer system from a client device, the host computer system being configured to store the site management program parameters for a site and generate for each controller of the site a controller program that implements the 20 controller's role in the site management program for the site, and to transmit the controller programs to the respective controller memories of the controllers, and to communicate with the controllers to initiate execution of the controller programs in accordance with the site management programs.

The client device may be any device suitable for communicating with the host computer system. Typically, the client device will be a personal computer. Preferably, the client device is adapted to communicate with the host computer system via the Internet. The client device may be a mobile telephone or the like.

The host computer system is preferably further configured to communicate with a controller to halt execution of the controller's controller program following receipt of a

10

15

25

30

stop command from a client responsible for the management of the site containing the controller, or from a or a person having the client's authority to issue the stop command.

The host computer system is preferably further configured to communicate with a controller to halt execution of the controller's controller program following generation of a stop command by the host computer system during execution of a site management program for the site containing the controller.

Preferably, the host computer system is also configured to:

- (a) receive parameters in respect of amendments to a site management program for a site from the client responsible for the management of the site or from a person having the client's authority to communicate the parameters;
- (b) generate a new controller program for each controller of the site that is affected by the amendments; and
- (c) transmit the new controller programs to the respective controller memories.

The host computer system may be further configured to receive an identifier from a person communicating with the host computer to verify that the person is the client or has the authority of the client to communicate with the host computer system.

Preferably the host computer system is further configured to supply the clients with software enabling the clients to effect the communication of the parameters.

The host computer system is preferably an Internet server.

The site management program in the host computer system preferably includes variable control logic that is in dependence on external data. The external data may be, or include, meteorological data. It may be, or include, Doppler radar data.

The present invention provides, in another aspect, a distributed system for remote management of a plurality of irrigation sites associated with clients who are responsible for the management of the sites, the distributed system servicing a plurality of clients, the distributed system comprising switching devices for irrigation equipment within the sites, a host computer system, and a plurality of client devices for enabling clients to communicate with the host computer system, each site having one or more controllers adapted to switch the switching devices of the site, each controller being adapted to execute a controller program and having controller memory for storing the controller program, the host

10

25

computer system being adapted to communicate with the controllers, wherein the system is configured to enable a client, or a person having the authority of the client, to communicate parameters for a site management program to the host computer system from a client device, and wherein the host computer system, following receipt of the parameters, generates for each controller of a site a controller program that implements the controller's role in the site management program, and transmits the controller programs to the respective controller memories, whereby to implement the site management program.

The host computer system of the distributed system is preferably further configured to communicate with a controller to halt execution of the controller's controller program following receipt of a stop command from a client device.

The host computer system of the distributed system is preferably further configured to communicate with a controller to halt execution of the controller's controller program following generation of a stop command by the host computer system during execution of a site management program for the site containing the controller.

- 15 Preferably, the distributed system is further configured to:
  - (a) enable a client, or a person having the authority of the client, to communicate parameters in respect of amendments to a site management program to the host computer system from a client device;
- (b) generate a new controller program for each controller of the site that is affected by
  the amendments; and
  - (c) transmit the new controller programs to the respective controller memories.

The distributed system may be further configured to enable a client, or a person having the authority of the client, to communicate an identifier to the host computer system using a client device, whereby to verify that the person is the client or has the authority of the client to communicate with the host computer system.

The host computer system of the distributed system may be configured to supply the clients' client devices with software enabling the clients to effect the communication of the parameters to the host computer system.

Preferably, the host computer system of the distributed system is an Internet server.

20

30

The site management program of the distributed system may include variable control logic that operates in dependence on external data. The external data may be, or include, meteorological data. It may be, or include, Doppler radar data.

#### Description of the drawings

5 The invention will now be further explained and illustrated by reference to the accompanying drawings in which:

Figure 1 is a schematic diagram showing a distributed system in accordance with a preferred embodiment of the present invention; and

Figure 2 is a schematic diagram showing further components of the distributed system of figure 1 that are associated with one site.

Figure 1 shows a distributed system, shown generally at 1, for remote management of a plurality of irrigation sites 90 containing switching devices for irrigation equipment. Distributed system 1 includes a host computer system 10, a plurality of client devices 20 and a plurality of controllers 40 associated with sites 90 containing switching devices in the form of triacs 72. The host computer system 10, client devices 20 and controllers 40 are all connected to the Internet, shown generally at 100.

Figure 2 shows further components of the distributed system associated with an irrigation site 90. Controllers 40 include a control section 50 and an output section 70. Control section 50 includes a communications interface 52 for communicating with the Internet 100, controller memory 54, and a processing unit 56 for executing controller programs held in memory 54 or transmitted from host computer system 10.

Output section 70 of controllers 40 includes triacs 72 for irrigation equipment 82 that are operable by processing unit 56. Triacs 72 are connected via field wiring 80 to field-installed irrigation equipment 82 in the respective sites 90.

25 The field wiring 80 carries 24V AC.

Host computer system 10 provides an Internet site for access by clients of the operators of host computer system 10, referred to hereafter as "the host website". A client enters the host website by means of a client device 20 capable of communicating with the Internet. Typically, client devices 20 will be personal computers operated by a client. The host website is a secure area for creating or amending the site management program in respect

10

15

20

25

30

of a client's site. The host website requires the client, or a person authorised by the client, to enter a password or other suitable identifier to verify the client's (or other person's) right to enter the host website.

Upon entry to the host website, the client will be able to create, or amend, a site management program in respect of the client's site or sites. Following entry into the host website, host computer system 10 sends a copy of software to the relevant client device 20 enabling the client to produce the site management program (or to amend an existing site management program). The host computer system 10 also sends details of the site management program as presently held by the host computer system 10 to the client device 20 so that the client (or person authorised by the client) may verify the state of the site management program at any time.

The host computer system 10 generates a site management program (or amended site management program) in respect of the client's site, based on input of relevant parameters from the client. Suitable parameters defining the site management program include parameters relating to when particular items of irrigation equipment are to be switched on and off by the switching devices, the combinations of switching devices to be employed, and parameters defining the logic underlying the site management program, including the definition of switching programs depending on the occurrence of various contingencies.

Once the parameters defining the site management program (or amended site management program) have been generated, the host computer system 10 generates a controller program for each controller of the site that participates in the site management program. The host computer system 10 then transmits the controller programs to the respective controller memories 52 of the relevant controllers 40.

At the appropriate time or times, as defined by the site management program, the host computer system 10 communicates with the relevant controllers 40 to initiate execution of the controller programs. When the controller programs are executed by the relevant controllers 40, the roles of the relevant controllers 40 in the site management program for the sites are thereby implemented.

The site management program may be manually overridden by the client (or a person authorised by the client) by enabling the host computer system 10 to communicate with controllers 40 to halt execution of the controllers' controller program following receipt of a

PCT/AU00/01158

stop command from a client (or authorised person) logged-on to the host computer system 10 by way of the host website.

The host computer system 10 is also configured so that a site management program can cause the host computer system 10 to communicate with controllers 40 to halt execution of the controllers' controller program following the generation of a stop command by the host computer system 10. For example, the site management program could generate a stop command or commands upon receipt of a signal indicating that rain is detected at the site or sites 90 in question.

The word 'comprising' and forms of the word 'comprising' as used in this description and in the claims does not limit the invention claimed to exclude any variants or additions. Modifications and improvements to the invention will be readily apparent to those skilled in the art. Such modifications and improvements are intended to be within the scope of this invention.

20

25

30

### THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

- 1. A method for remote management of a plurality of irrigation sites associated with clients who are responsible for the management of the sites, each site having one or more controllers adapted to switch switching devices for irrigation equipment within the site, each controller being adapted to execute a controller program and having controller memory for storing the controller program, the method comprising:
  - (a) receiving from at least one of the clients, and storing in a host computer system, parameters for a site management program for one of the sites with which the client is associated;
- 10 (b) generating a controller program for each controller of the site, the controller program being adapted to implement the controller's role in the site management program for the site;
  - (c) transmitting the controller programs to the respective controller memories of the controllers; and
- 15 (d) communicating with the controllers to initiate execution of the controller programs in accordance with the site management programs.
  - 2. A method according to claim 1 further comprising the step of communicating with a controller to halt execution of the controller's controller program following receipt of a stop command from a client responsible for the management of the site containing the controller, or from a or a person having the client's authority to issue the stop command.
  - 3. A method according to claim 1 or claim 2 further comprising the step of communicating with a controller to halt execution of the controller's controller program following the generation of a stop command by a computer system implementing a site management program for the site containing the controller.
  - 4. A method according to any one of the preceding claims further comprising the steps of receiving parameters in respect of amendments to a site management program for a site from the client responsible for the management of the site or from a person having the client's authority to communicate the parameters, generating a new controller program for each controller of the site that is affected by the amendments, and transmitting the new controller programs to the respective controller memories.

PCT/AU00/01158

- 5. A method according to any one of the preceding claims further comprising the steps of providing each client with a unique identifier, and receiving an identifier from a person prior to implementing parameters received from the person to verify that the person is the client or has the authority of the client to communicate the parameters.
- A method according to any one of the preceding claims further comprising the step of supplying the clients with software enabling the clients to effect the communication of the parameters.
  - 7. A method according to any one of the preceding claims wherein the site management program includes variable control logic that is in dependence on external data.
- 10 8. A method according to claim 7 wherein the external data is, or includes, meteorological data.
  - 9. A method according to claim 7 wherein the external data is, or includes, Doppler radar data.
- 10. A method according to any one of the preceding claims substantially as described herein with reference to the drawings.
- A host computer system for remote management of a plurality of irrigation sites 11. associated with clients who are responsible for the management of the sites, each site having one or more controllers adapted to switch switching devices for irrigation equipment within the site, each controller being adapted to execute a controller program and having controller memory for storing the controller program, the host 20 computer system servicing a plurality of clients and being adapted to communicate with the controllers and with client devices whereby to enable a client, or a person having the client's authority, to communicate parameters for a site management program to the host computer system from a client device, the host computer system 25 being configured to store the site management program parameters for a site and generate for each controller of the site a controller program that implements the controller's role in the site management program for the site, and to transmit the controller programs to the respective controller memories of the controllers, and to communicate with the controllers to initiate execution of the controller programs in 30 accordance with the site management programs.
  - 12. A host computer system according to claim 11 further configured to communicate with a controller to halt execution of the controller's controller program following

receipt of a stop command from a client responsible for the management of the site containing the controller, or from a or a person having the client's authority to issue the stop command.

- 13. A host computer system according to claim 11 or claim 12 further configured to

  communicate with a controller to halt execution of the controller's controller program

  following generation of a stop command by the host computer system during

  execution of a site management program for the site containing the controller.
  - 14. A host computer system according to any one of claims 11 to 13 further configured to:
    - (a) receive parameters in respect of amendments to a site management program for a site from the client responsible for the management of the site or from a person having the client's authority to communicate the parameters;
    - (b) generate a new controller program for each controller of the site that is affected by the amendments; and
    - (c) transmit the new controller programs to the respective controller memories.
- 15. A host computer system according to any one of claims 11 to 14 further configured to receive an identifier from a person communicating with the host computer to verify that the person is the client or has the authority of the client to communicate with the host computer system.
- 16. A host computer system according to any one of claims 11 to 15 further configured to supply the clients with software enabling the clients to effect the communication of the parameters.
  - 17. A host computer system according to any one of claims 11 to 16 further configured to be an Internet server.
- 18. A host computer system according to any one of claims 11 to 17 wherein the site

  25 management program includes variable control logic that is in dependence on external data.
  - A host computer system according to claim 18 wherein the external data is, or includes, meteorological data.
- 20. A host computer system according to claim 18 wherein the external data is, or includes, Doppler radar data.

PCT/AU00/01158

12

21. A host computer system according to any one of claims 11 to 20 substantially as described herein with reference to the drawings.

WO 01/22177

25

30

- A distributed system for remote management of a plurality of irrigation sites associated 22. with clients who are responsible for the management of the sites, the distributed system servicing a plurality of clients, the distributed system comprising switching 5 devices for irrigation equipment within the sites, a host computer system, and a plurality of client devices for enabling clients to communicate with the host computer system, each site having one or more controllers adapted to switch the switching devices of the site, each controller being adapted to execute a controller program and 10 having controller memory for storing the controller program, the host computer system being adapted to communicate with the controllers, wherein the system is configured to enable a client, or a person having the authority of the client, to communicate parameters for a site management program to the host computer system from a client device, and wherein the host computer system, following receipt of the parameters, generates for each controller of a site a controller program that 15 implements the controller's role in the site management program, and transmits the controller programs to the respective controller memories, whereby to implement the site management program.
- 23. A distributed system according to claim 22 wherein the host computer system is

  further configured to communicate with a controller to halt execution of the

  controller's controller program following receipt of a stop command from a client

  device.
  - 24. A distributed system according to claim 22 or claim 23 wherein the host computer system is further configured to communicate with a controller to halt execution of the controller's controller program following generation of a stop command by the host computer system during execution of a site management program for the site containing the controller.
    - 25. A distributed system according to any one of claims 22 to 24 further configured to:
    - enable a client, or a person having the authority of the client, to communicate parameters in respect of amendments to a site management program to the host computer system from a client device;

- (b) generate a new controller program for each controller of the site that is affected by the amendments; and
- (c) transmit the new controller programs to the respective controller memories.
- A distributed system according to any one of claims 22 to 25 further configured to
  enable a client, or a person having the authority of the client, to communicate an
  identifier to the host computer system using a client device, whereby to verify that the
  person is the client or has the authority of the client to communicate with the host
  computer system.
- 27. A distributed system according to any one of claims 22 to 26 wherein the host computer system is configured to supply the clients' client devices with software enabling the clients to effect the communication of the parameters to the host computer system.
  - 28. A distributed system according to any one of claims 22 to 27 wherein the host computer system is an Internet server.
- 15 29. A distributed system according to any one of claims 22 to 28 wherein the site management program includes variable control logic that operates in dependence on external data.
  - 30. A distributed system according to claim 29 wherein the external data is, or includes, meteorological data.
- 20 31. A distributed system according to claim 29 wherein the external data is, or includes,

  Doppler radar data.
  - 32. A distributed system according to any one of claims 22 to 31 substantially as described herein with reference to the drawings.





Figure 1



### INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU00/01158

			UUU/01158					
Α.	CLASSIFICATION OF SUBJECT MATTER							
Int. Cl. 7:	G05B 15/00, 19/414; G06F 15/16, 17/60, 19/00; A01G 25/16							
According to	International Patent Classification (IPC) or to both	national classification and IPC						
	FIELDS SEARCHED							
Minimum docu IPC: G05B 1	mentation searched (classification system followed by cl 5/00, 19/414; G06F 15/16, 17/60, 19/00; A010	lassification symbols) G 25/16						
Documentation	searched other than minimum documentation to the ext	ent that such documents are included in t	he fields searched					
Electronic data DWPI, US I	base consulted during the international search (name of DATABASE: with keywords (eg control, manage	data base and, where practicable, scarch	terms used)					
C.	DOCUMENTS CONSIDERED TO BE RELEVANT							
Category*	Citation of document, with indication, where app	propriate, of the relevant passages	Relevant to claim No.					
х	WO 95/22799 A (WATERLINK SYSTEMS Entire document	1-32						
x	US 4626984 A (UNRUH et al) 2 December Entire document	1-32						
x	WO 97/08942 A (SMART RAIN CORP.) 12 Entire document	1-32						
x	Further documents are listed in the continuation	on of Box C X See patent fam	nily annex					
* Special categories of cited documents:  "A" document defining the general state of the art which is not considered to be of particular relevance  "E" earlier application or patent but published on or after the international filing date  "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  "O" document referring to an oral disclosure, use, exhibition or other means  "P" document published after the international filing date or priority date and not in conflict with the application but cited understand the principle or theory underlying the invention cannot be considered novel or cannot be considered to involve an inventive step when the document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document of combined with one or more other such documents, such combination being obvious to a person skilled in the art document member of the same patent family								
Date of the act	tual completion of the international search	Date of mailing of the international sea	rch report					
25 October Name and mai	2000 iling address of the ISA/AU	Authorized officer						
PO BOX 200, E-mail addres	N PATENT OFFICE WODEN ACT 2606, AUSTRALIA s: pct@ipaustralia.gov.au (02) 6285 3929	A. SEN Telephone No : (02) 6283 2158						

#### INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU00/01158

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT					
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.			
х	WO 90/03724 A (SOLATROL) 19 April 1990 Entire document	1-32			
x	WO 87/04275 A (AUDITEL SYSTEMS) 16 July 1987 Entire document	1-32			
x	US 4760547 A (DUXBURY) 26 July 1988 Entire document	1-32			
	·				

## INTERNATIONAL SEARCH REPORT Information on patent family members

International application No. PCT/AU00/01158

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Doo	rument Cited in Search Report	Patent Family Member					
wo	9522799	AU	17004/95	US	5696671	US	5870302
US	4626984	NONE					
wo	9708942	AU	68672/96	AU	68674/96	EP	852459
		US	5740031	wo	9709612		
wo	9003724	AU	44183/89	CA	2000139	EP	399006
		US	5173855				<del></del>
wo	8704275	AU	68428/87	EP	252131		
US	4760547	NONE					
							END OF ANNI